North America's Leader in Hazardous Material Information Management

1905 Aston Avenue, Carlsbad, CA 92008 Phone (800) 451-8346 Fax (760) 602-8888

MSDS PRODUCT INFORMATION

Date: 10/07/2005

To: MSDS Requester

From: 3E Company

Subject: The MSDS you have requested

[] MSDS NOT REQUIRED

In response to your request for a Material Safety Data Sheet, according to the OSHA Hazard Communicatin Standard (Right-to-Know), the following item is an article. Articles are defined in 29 CFR 1910.1200(c). Products such as Drugs, cosmetics, food, or alcoholic beverages, wood or wood products, and tobacco or tobacco products, as defined in 29 CFR1910.1200(b)(6), are exempt from the Hazard Communication Standard. Items that are considered articles, as defined in 29 CFR 1910.1200(c), are also exempt from this Standard. Therefore, the manufacturer is not required to provide an MSDS for this product.

[X] MSDS DISCONTINUED PRODUCT

In response to your request for a Material Safety Data Sheet, the manufacturer has discontinued the product listed below. The MSDS Attached is the most current version, or an MSDS is no longer available.

[] MSDS BEST COPY AVAILABLE

The MSDS attached is the best copy available from the manufacturer.

[] MANUFACTURER NO LONGER IN BUSINESS

In response to your request for a Material Safety Data Sheet, a current MSDS could not be obtained for this product. It has been determined that the manufacturer listed below is no longer in business. A current address and phone number could not be located.

Manufacturer: Lone Star Drywall Mfg. Co.

Product Name: Lone Star, Ready Mixed, All Purpose, Joint Compaund (DISCONTINUED)



PREPARED BY: L. Ehrhardt DATE PREPARED: March 20,1997 ISSUED: March 20, 1997

MATERIAL SAFETY DATA SEEETS

Lone Star Drywall Mfg. Co. 201 S. Catherine Terrell, Texas 75160 Plant: 214/563-7857 Dallas office: /288-7527

SECTION I

PRODUCT: Lone Star Ready-Mix Joint Compound Top-Pro, Lone Star, Big Red Label

DATE: March 20, 1997

CHEMICAL PARILY: Calcium Carbonate, Poly Vinyl Acetate

SECTION II - HAZARDOUS INCREDIENTS

 MATERIAL:
 2
 TLV (units)
 CAS \$

 Troysan #174
 1/8th of 1%
 Not Established
 #34375-28-5

SECTION III - PHYSICAL DATA

STATE: (H²0=1):1.4

PERCENT VOLATILE BY VOLUME: 35%

APPEARANCE AND ODOR: off white paste, low odor

SECTION IV - FIRE AND EXPLOSION DATA

FLASH PONT: None

EXTINGUISHING NEDIUM: Not Combustible
SPECIAL FIRE PIGETING PROCEDURES: None
UNUSUAL FIRE AND EXPLOSION BAZARDS: None

SECTION V - HEALTH HAZARD DATE

EFFECTS OF OVEREXPOSURE: If dry sanded, inhalation of dust may be irritating to eyes and nose. Long term exposure could cause lung injury due to clay content. Repeated inhalation of respirable dust in excess may cause chronic respiratory disorder due to calcium content. When sanding always wear an NOISH approved dust respirator.

EMERGENCY AND FIRST AID PROCEDURES:

EYES: Flush thoroughly with water. If irratation persists consult physician.

SKIN: Wash with soap and water.
INGESTION: Consult physician.
INHALATION: Get to Fresh air area.

SECTION VI - REACTIVITY DATA

STABILITY: Stable

HAZARDOUS POLYMERIZATION: Won't occur

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO TAKE IF SPILLED OR LEAKED OUT: Scoop up. Wash with water before drying.

WASTE DISPOSAL METHOD: Use Federal, State, and Local regulations get to sanitary landfill.

SECTION VIII - SPECIAL PROTECTION INFO.

RESPIRATORY PROTECTION: None normally necessary.

VENTILATION: Local exhaust to keep dust in air below TLV.

PROTECTIVE EQUIPMENT: Safety glasses

SECTION 1X - SPECIAL PRECAUTIONS

Store in a dry place.